

Sounder-Beacon Units

ROLP LX WALL

How you benefit:

- | Ultra low current consumption
- | Up to 7.5 m coverage volume
(switchable to 2.5 m)
- | 0.5 Hz or 1.0 Hz flash rate
- | Use where current consumption
is a key consideration
- | Delivering up to 106 dB(A) sound output
- | Ideal for bedrooms, bathrooms and toilets
- | Switch flash rate to 0.5 Hz to reduce
current consumption
- | EN54-23 conform

SPECIFICATIONS

Model	ROLP LX WALL (Base)	SOUNDER
Current consumption	22 – 37 mA dependent on settings	3 – 32 mA/15 mA @ DIN-Tone
Operating Voltage	9 – 15 V DC (Fire Use) / 18 – 28 V DC (Fire Use) / 9 – 28 V DC (Non fire Use)	9 – 28 V DC
IP rating	IP65	IP65
Approvals	VdS (G214070)	VdS (G206019), CPD, LPCB, CNPP, UL
Sound output	102 dB(A) @ DIN-Tone	64 – 112 dB(A) / 103 dB(A) @ DIN-Tone
Operating temperature	-25 °C to +70 °C	-25 °C to +70 °C
Body colour	white or red	white or red
Coverage (y)	7.5 m (switchable to 2.5 m)	
Sound output	W-2,4-7,5 (135 m³)	
Coverage Volume Code	1 Hz (switchable to 0.5 Hz)	
LED colours	white or red	

Zeichnung

