

Sounder-Beacon Units

SYMPHONI LX WALL

How you benefit:

- | Ultra low current consumption
- | Up to 7.5 m coverage volume
(switchable to 2.5 m)
- | 0.5 Hz or 1.0 Hz flash rate
- | Coverage switch to 2.5 m
- | Use where current consumption
is a key consideration
- | Ideal for bedrooms, bathrooms and toilets
- | Switch flash rate to 0.5 Hz to reduce
current consumption
- | Reduces power consumption by up to 50 %
- | EN54-23 conform

SPECIFICATIONS

Model	SYMPHONI LX WALL (Base)	SOUNDER
Current consumption	15 – 30 mA dependent on settings	190 – 260 mA / 240 mA @ DIN-Tone
Operating Voltage	18 – 28 VDC (Fire Use) / 12 – 28 VDC (Non fire Use)	9 – 28 V DC
IP rating	IP21C	IP21C
Approvals	VdS (G214071)	VdS (G206027), CPD
Sound output	112 dB(A) @ DIN-Tone Symphoni HO	88 – 120 dB(A) / 112 dB(A) @ DIN-Tone
Operating temperature	-10 °C to +55 °C	-10 °C to +55 °C
Body colour	white or red	white or red
Coverage (y)	7.5 m (switchable to 2.5 m)	
Mounting height (x)	2.4 m (max.)	
Sound output	W-2.4-7.5 (135 m³)	
Coverage Volume Code	1 Hz (switchable to 0.5 Hz)	
LED colours	white or red	

Zeichnung

